

Eliciting implicit assumptions of proofs in the Mizar Mathematical Library by property omission

Jesse Alama¹

the date of receipt and acceptance should be inserted later

Abstract When formalizing proofs with interactive theorem provers, it often happens that extra background knowledge (declarative or procedural) about mathematical concepts is employed without the formalizer explicitly invoking it, to help the formalizer focus on the relevant details of the proof. In the contexts of producing and studying a formalized mathematical argument, such mechanisms are clearly valuable. But we may not always wish to suppress background knowledge. For certain purposes, it is important to know, as far as possible, precisely what background knowledge was implicitly employed in a formal proof. In this note we describe an experiment conducted on the Mizar Mathematical Library of formal mathematical proofs to elicit one such class of implicitly employed background knowledge: properties of functions and relations (e.g., commutativity, asymmetry, etc.).

1 Introduction

When formalizing mathematical proofs with interactive theorem provers, it often happens that extra background knowledge is employed without the formalizer explicitly invoking it. The effect is clear: thanks to such facilities, the formalizer can focus more on the relevant details of the proof he is working on, rather than (relatively more) tedious “details”. In the contexts of producing and studying a formalized mathematical argument, such mechanisms are important and deserve to be strengthened.

But we may not always wish to suppress background knowledge. For certain purposes, it is important to know, as far as possible, precisely what background

The author was supported by the FCT project “Dialogical Foundations of Semantics” (Di-FoS) in the ESF EuroCoRes programme LogICCC (FCT LogICCC/0001/2007).

Center for Artificial Intelligence
New University of Lisbon
E-mail: j.alama@fct.unl.pt

knowledge was implicitly employed in a formal proof. There are a number of practical applications of such information, such as facilitating theory exploration [?], library recompilation [?], improved machine learning about formal proofs, premise selection heuristics, etc. The aim of eliciting exactly what is used is also important philosophically, because we come closer to finding what is truly necessary for the success of a theorem. Our project thus aligns in a modest way with the overall aims of reverse mathematics [?], a vibrant branch of contemporary proof theory whose aim is to discover axioms from theorems (rather than the other way around).

The task of eliciting all implicit information of a formalized mathematical proof is a stimulating challenge. Various approaches can be used depending on the ITP and its associated logic(s). (For a comparison of how this can be done for *Mizar* as compared to *Coq*, see [?].) In this note we describe an experiment conducted on the *Mizar* Mathematical Library (MML) of formal mathematical proofs to elicit one such class of implicitly employed background knowledge: properties of functions and relations (e.g., commutativity, asymmetry, etc.). We employ the term **constructor** to mean function or relation in a formal mathematical library.¹ The MML is a large collection of formal mathematical proofs expressed in classical first-order set theory and a natural deduction-style declarative proof formalism. (For an introduction to *Mizar*, see [?].) Analogous experiments could clearly be performed on other libraries of formalized mathematical knowledge. The *Mizar* system is especially attractive for this kind of experiment because of the clear semantics of the properties that can be implicitly attached to functions and relations (they are simple universal first-order formulas) and the relative ease of manipulating these properties.

Section 2 outlines some previous related work and sketches some of the intended applications of the constructor property dependency data. Section 3 gives two examples of how constructor properties can be implicitly used in formal proofs in *Mizar*. Section 4 describes the method we used to make explicit the constructor properties that are needed for *Mizar* inferences. The heart of the paper is Section 5, where we give the results of our computation about needed and unneeded constructor properties for the entire *Mizar* Mathematical Library.

2 Applications and previous work

Mizar’s notion of constructor properties (and another mechanism for suppressing the premises of an inference, so-called requirements) are a relatively new invention for *Mizar* [?]. The information that a constructor property is needed for an inference can be exploited in various ways. One potential application is to use the needed-property information as an indication of what formula shapes are useful in the search for a successful proof. Building on the ideas of

¹ The term “constructor” is in fact part of the *Mizar* idiolect for formal mathematics. There are more kinds of objects that count as “constructors” in *Mizar*—such as structures—but in this paper we are interested only in functions and predicates.

S. Shulz [?], one would strip away the actual symbols employed in a proof that implicitly relies on some constructor property, thereby learning some structural information about what contributes to the success of a theorem. One could profitably use this information to assist in the problem of selecting candidate premises in large ATP problems [?]. More generally, such a structural approach can give us some information about shapes of successful patterns of formal reasoning.

The information that a property of a constructor is not needed indicates, *prima facie*, that one is dealing with a kind of generalization. It may not always be clear, though, how to use this information to craft generalizations. The problem lies in the familiar distinction in logic between reasoning formally about a class of structures or about a single structure. It would seem that information that a property is not needed is more useful in cases of reasoning about classes of structure (e.g., about fields), but in the case of reasoning about “concrete” mathematical objects (a single structure, e.g., the real numbers). Thus, we may find in a theorem about real numbers that commutativity of addition is not used. One could immediately construct a generalization of such a theorem to a class of structures that are just like the real numbers, but in which the commutativity of addition is not assumed. The value of such a generalization may not be clear. By contrast, imagine we encounter a theorem about fields in which the commutativity of the field’s addition operation is not used. In this case, the generalization procedure is similar to the procedure used in the case of the reals. By contrast, though, the significance and utility of such a generalization is clearer because the reasoning was already about a wide class of structures, the properties of whose functions and relations enjoyed some flexibility.

One might imagine an advisor attached to an interactive theorem prover that can use the information that a constructor property is needed to help one investigate and formulate suitable generalizations. As discussed earlier, one relevant task (which seems quite interesting from the perspective of artificial intelligence) would be to decide whether a generalization is even warranted. It’s intuitively clear that when we use a mathematical concept in a proof we use only some aspects of it and not others; at some steps, we require one thing of a concept, but at other steps we require something else. Dividing a concept so that we never require from it nothing less than its “full content” every time it is used seems like a drastic suggestion. Still, we may find value in a mitigated form of this advice.

3 Omitting properties of functions and relations

In *Mizar*, one can **attach** properties to functions and relations; Tables 1 and 2 lays out all nine properties currently supported by *Mizar*. These properties are used by the *Mizar* verifier as “background knowledge” that doesn’t need to be cited by a formalizer.

Relation Property	Formula
reflexivity	$\forall x[R(x, x)]$
symmetry	$\forall x\forall y[R(x, y) \rightarrow R(y, x)]$
asymmetry	$\forall x\forall y[R(x, y) \rightarrow \neg R(y, x)]$
connectedness	$\forall x\forall y[R(x, y) \vee R(y, x)]$
irreflexivity	$\forall x[\neg R(x, x)]$

Table 1 Properties of relations in Mizar

Function Property	Formula
projectivity	$\forall x[f(f(x)) = f(x)]$
involutiveness	$\forall x[f(f(x)) = x]$
idempotence	$\forall x[g(x, x) = x]$
commutativity	$\forall x\forall y[g(x, y) = g(y, x)]$

Table 2 Properties of functions in Mizar

3.1 Example 1: Relation property

Consider the definition of the proper subset relation:

```

1 definition
2   let X,Y be set;
3   pred
4     X c< Y
5   means
6     X c= Y & X <> Y;
7   irreflexivity;
8   asymmetry;
```

This example, taken from the Mizar article XB00LE_0, defines the predicate (**pred**) of one set X being a proper subset $c<$ of another Y . The symbols $c=$ and $<>$ denote the subset relation and disequality, respectively. The keywords **irreflexivity** and **asymmetry** included in the definition indicate that the proper subset relation will henceforth have the properties of irreflexivity and asymmetry; inferences involving the proper subset relation will implicitly use these properties.

There are 58 occurrences in the Mizar Mathematical Library in which the irreflexivity of the proper subset relation is implicitly used. Here is one example, taken from the article TREES_1:

```

1 theorem
2   not <*n*> is_a_proper_prefix_of <*m*>
3 proof
4   assume A1: not thesis;
5   then <*n*> is_a_prefix_of <*m*> by XB00LE_0:def 8;
6   hence contradiction by A1,Th16;
```

```
7 end;
```

The theorem says that the one-term sequence whose sole term is the number n is not a proper prefix of the one-term sequence whose sole term is the number m . The binary relation `is_a_prefix_of` on finite sequences is defined simply as set inclusion. The reference `Th16` refers to the theorem that says that a one-term finite sequence $\langle s \rangle$ is a prefix of the one-term finite sequence $\langle t \rangle$ iff $s = t$. The proof of our theorem goes by contradiction. Note that the symbol for the proper subset relation, $\subset$, occurs neither in the theorem nor in the proof. In the absence of the assumption that $\subset$ is irreflexive, the contradiction at the end of the proof does not follow. A contradiction indeed does not follow: we get from `Th16` that $n = m$, but this is compatible with the one-term sequence $\langle n \rangle$ being a proper subset of $\langle m \rangle$, if we haven't assumed that the proper subset relation is irreflexive.

3.2 Example 2: Function property

Additive magmas come equipped, of course, with an addition operation $+$. In the case of abelian additive magmas, we know that $+$ is commutative:

```
1 definition
2   let V be Abelian addMagma,
3       v be Element of V,
4       w be Element of V;
5   redefine func v + w;
6   commutativity;
7 end;
```

This example is taken from the Mizar article `RLVECT_1`. The keyword `redefine` here does not indicate that we are changing the definiens of the binary function $+$ on elements of additive magmas (which in any event is essentially undefined); rather, we are attaching the property of commutativity to $+$. Such an operation is obviously admissible because of the definition of what it means for an additive magma to be abelian.

As an example of an inference that implicitly depends on the commutativity of $+$, consider:

```
1 theorem
2   for L being add-associative right_zeroed
3       right_complementable Abelian
4       non empty addLoopStr,
5       b, c being Element of L
6       holds c = b - (b - c)
7 proof
8   let L be add-associative right_zeroed
9       right_complementable Abelian
```

```

10      non empty addLoopStr,
11      b, c be Element of L;
12      set a = b - c;
13      a+c-a = c-a+a by RLVECT_1:28
14      .= c by Th1;
15      hence thesis by Th1;
16 end;

```

Ignoring the definition of all the attributes that are being attached to the type `addLoopStr` (viz., an additive Moufang loop structure), the crucial step here is the equation on line 17. Note that the terms `a` and `c` are being swapped without reference to the commutativity of $+$ (the reference to the theorem `RLVECT_1:28` is not relevant here).

4 Eliciting needed implicit constructor properties

To elicit the constructor properties that are needed for an item of the Mizar Mathematical Library, we exploit Mizar’s separation of (i) the construction of the environment in which verification will be carried out from (ii) the process of verification properly speaking.

In step (i), Mizar constructs an environment for verification, importing all constructors that occur explicitly or implicitly in a Mizar text. If a constructor has a property associated with it, the environment will contain the property attached to the constructor, regardless of whether it is truly needed. The environment is thus a conservative overestimate of what is truly needed for the verification to succeed. By intervening between the construction of the environment and the verification proper, one can manipulate the environment in which the verification is carried out. We simply remove a property attached to a constructor and carry out the verification; if the verification succeeds, we know that the property of the construction was not actually needed.

Thanks to the use of XML as the representation of the environment for Mizar articles [?], conducting our experiment is as simple as applying certain XSL stylesheets to the environment files.

Rather than operating on whole Mizar articles, which generally contain dozens if not hundreds of toplevel items, we operate on a individual theorems of the MML. This is made possible by dividing the MML into fine-grained “items” (which are in fact valid Mizar “microarticle”); see [?] for more information on how this decomposition of the MML is carried out.

5 Usage of properties throughout the MML

We have so far said that a verifiable item I of the Mizar Mathematical Library depends on property P of constructor C just in case I , in the absence of the attachment of P to C , is not verifiable. This definition of dependence upon a constructor property fails to capture the dependence of one item upon

Property	Direct Items	Indirect Items
reflexivity	54113	102426
symmetry	29744	97220
asymmetry	256	82585
connectedness	5020	83083
irreflexivity	91	65951
projectivity	153	10002
involutiveness	533	67853
idempotence	535	70132
commutativity	14055	92580

Table 3 Direct and indirect dependence upon properties in the MML

another. For example, suppose that an item I does not depend on property P of constructor C , that is, I is verifiable if one detaches from C the property P . Suppose, though, that item I depends on some other item I' which *does* need property P of C . Such a though experiment suggest that we distinguish two sense of “need”: direct and indirect.

Definition 1 Item I **directly needs** property P of constructor C iff verification of I will fail if P is detached from C .

Item I **indirectly needs** property P of C iff I directly needs P of C or there exists an item I' such that I depends on I' and I' needs P of C .

Both senses of “need” are useful. Table 3 gives statistics about various constructor properties that are needed directly and indirectly in the MML.

There are a number of fascinating details behind these statistics:

- Reflexivity is directly needed by nearly half of the items of the Mizar Mathematical Library, and is indirectly needed by nearly the entire library. Reflexivity of equality of sets accounts for this: it is indirectly needed by fully 102242 items. It is perhaps not surprising that such a fundamental property of a built-in logical notion pervades the library.
Putting aside equality, the next most important reflexive constructor is subset inclusion, which is indirectly needed by 93284 items. A redefinition of subset inclusion for ordinals is indirectly used by 8279 items. Putting aside these “logical” or “set theoretical” examples, the most important reflexive “mathematical” relation is the less-than-or-equal-to relation $\leq$ on (extended) real numbers, whose reflexivity is indirectly needed by 67196 items.
- Irreflexivity is directly needed by only a handful of items in the library, but indirectly it supports about 2/3 of the library. The explanation is the proper subset relation: the irreflexivity of this constructor is needed by 65546 items. The most important “mathematical” example is the relation of one element of a relation being strictly less than another.
- Asymmetry is attached to only five constructors in the entire MML:
 - $\in$ (set membership);

-
- the proper subset relation;
 - a variant of $\in$, defined for many-sorted set structures;
 - the strictly-lexicographically-less-than relation on finite tuples of natural numbers;
 - the strictly-lexicographically-less-than relation on bags of ordinals.
 - The asymmetry, of $\in$, is foundationally significant in the sense of mathematical logic (it expresses a weak form of the axiom of foundation) and for the Mizar Mathematical Library. The asymmetry of this constructor alone accounts for essentially all items that need the asymmetry of any constructor: 82581 items indirectly need this weak form of foundation, whereas only 283 items directly depend on this property of $\in$.²
 - Likewise, projectivity is rarely directly needed, but supports a substantial piece of the library. Interestingly, it is the closure operation defined on subsets of a topological space³ that accounts for the lion's share of the items that indirectly need an projective constructor: 7536 items depend on the projectivity of the closure operation.
 - Connectedness is attached to very few constructors of the Mizar Mathematical Library, but the constructors to which this property is attached have a significant influence across the MML. The constructor whose connectedness is used indirectly by the greatest number of items is the subset relation, restricted to ordinals. The connectedness of this constructor expresses a rather significant fact about ordinals (any two ordinals are comparable). The proof of this fact in Mizar uses a trichotomy-like principle for ordinals, saying that for any two ordinals A and B , either $A \in B$, $A = B$, or $B \in A$. The connectedness of the subset relation on ordinals is indirectly needed by 82490 items. The next most significant example is $\leq$ on rational numbers, indirectly needed by 71313 items.
 - Involutiveness also requires some explanation. There are two items that vie for the most important here:
 - The sign-changing operation $x \mapsto -x$ on real numbers is needed by 65501 items.
 - The reciprocal operation $z \mapsto 1/z$ on complex numbers is needed by 65105 items.
- The constructor with the next highest number of items that indirectly depend on its involutiveness is the relative complement operation, which is indirectly needed by 8847 items.
- The constructor whose idempotence is most frequently needed indirectly is the binary union of two sets, which is indirectly needed by 69184 items. The idempotence of binary set intersection takes second place: it is indirectly needed by 24249 items.

² This is arguably a curiosity of the organization of the MML. It turns out that asymmetry of $\in$ is used very early on in the logical construction of the MML, hence its outsized influence.

³ To be precise, the operation is defined not on topological *spaces*, but on topological *structures*, which one can think of simply as a class of structures that has a carrier and a topology, viz., a collection of subsets of the carrier. A topological structure on its own is not assumed to have any properties beyond these.

- Several items in the Mizar Mathematical Library indirectly depend on more than 100 constructor properties. The item with the greatest number of dependencies is taken from the proof of the Jordan curve theorem:

```

1 theorem
2   for n being Element of NAT
3   for C being being_simple_closed_curve
4     Subset of (TOP-REAL 2)
5     st n is_sufficiently_large_for C
6     holds cell(Gauge(C,n),
7               X-SpanStart(C,n) - '1,
8               Y-SpanStart(C,n))
9     misses C
10 proof
11   assume n is_sufficiently_large_for C;
12   then cell(Gauge(C,n),
13           X-SpanStart(C,n) - '1,
14           Y-SpanStart(C,n)) c= BDD C by Th6;
15   hence thesis by JORDAN1A:15,XBOOLE_1:63;
16 end;
```

The precise mathematical definitions, the theorem references (Th6, JORDAN1A:15, etc.) and the proof here are not important. What is important is that we are dealing here with a very short proof (it has only three steps) of a theorem along the way to a substantial landmark in formal mathematics. Despite appearances, this theorem indirectly depends on fully 113 constructor properties.

The formalization in Mizar of the Jordan curve theorem required a great deal of work and made heavy use of the Mizar system's features, such as its support for constructor properties under discussion here. We see this by virtue of the fact that the theorems of the series of Mizar articles leading to the final proof of the Jordan curve theorem indirectly need, on average, several dozen constructor properties.

6 Conclusion and future work

The abstractions discovered here in the context of an interactive theorem prover could, in all probability, be discovered equally well by an ATP. With an automated theorem prover one could, in principle, go much further than we have gone here. An infrastructure for carrying out such exploration (sound translation of Mizar proofs to a vanilla unsorted first-order language, infrastructure for constructing and working with the associated ATP problems, etc.) already exists [?]. One could even verify the dependency claims made here outside of Mizar, in the style of [?].

When we discover that some property of a function or relation is needed, we are discovering not that the property is logically or mathematically needed for

the success of the theorem in question; instead, we are discovering only that there exists a formal deduction (viz., a **Mizar** proof) where this property is used. It is certainly quite possible that there would exist other formal proofs of the same theorem that do not use the property. This suggests a much more ambitious project: discovering *new proofs* of theorems that use much less than what an interactively constructed proof uses. Such prospects are enticing, and deserve to be carried out. Such a project naturally also bears on the philosophical problem of when two proofs are “the same”: it could very well be that there are two proofs of the same theorem, one which exploits a property of a function or relation, and another which doesn’t, but which should nonetheless, from another perspective, be considered identical.

Constructor properties are but one mechanism in **Mizar** that hides premises of inferences. **Mizar** also supports so-called requirements, which also help to allow one to reason validly without having to be explicit about precisely what premises are needed for every inference of a proof. **Mizar** also has some built-in functionality concerning arithmetic. Both of these mechanisms are of great value for the formalizer when constructing a formal proof, but if one is interested in making explicit premises that were suppressed during proof construction, **Mizar**’s requirements and arithmetic facilities need to be taken into account.

One might wonder why there are only the nine constructor properties supported by **Mizar**. Binary relation transitivity, unary function surjectivity and injectivity, for example, are conspicuously absent. Supporting such additional function and relation properties could be quite valuable; **Mizar** itself and tools using its library could exploit function injectivity and surjectivity, for example, to help rule out the solution for certain search problems that require the domain of discourse to be finite (see [?]). But more generally, it would be valuable to mine the **Mizar** Mathematical Library for common shapes of formulas that play a large inferential role, and which could naturally be promoted to the level of constructor properties. One might discover fruitful properties that could help make formalization in **Mizar** even more appealing and practical.